PJ-202DL-EB

Bidirectional Projection Speaker

The PJ-202DL-EB is certified according to the European Standard EN 54-24: 2008, and compliant with the British Standard BS 5839-8: 2008 14.8. The PJ-202DL-EB is a bidirectional projection speaker designed for wall or ceiling installation in indoor and outdoor applications.



Order no: PJ-202DL-EB
Alternative products: VX-3008F, VX-3004F, VX-3016F, SX-2000SM, SX-2000AO, SX-2100AO, VX-2000, VM-3360VA, VM-3240VA, VM-3240E, VM-3360E, VP-3504, VP-3154, VP-3304, VP-2421, VP-2421incl, VP-2241, VP-2241incl, VP-2122incl, VP-2122, VP-2064, VP-2064incl

Specifications

Frequency response	120 Hz - 20 kHz
Connection	Ceramic screw terminals, thermal fuse, external connection box, 5-wire BS-compliant
Sensitivity (1#W, 1#m) (combined)	88 dB (100 Hz - 10 kHz, pink noise)
Speaker component	5“ P.P. cone + HC x 2
Rated input	20 W
Tappings	20 / 10 / 5 W (100 V), 10 / 5 / 2.5 W (70 V)
Rated impedance	100 V, 70 V
Dimensions (W x H x D)	x 186
Dimensions (ø x D)	146 x 186 mm
Finish	Aluminium, white

We supply sound, not equipment.
www.toa.eu

©TOA Electronics Europe GmbH | Data subject to change without notice.
EN, 2019/01/22

PJ-202DL-EB

Bidirectional Projection Speaker

Appearance

©TOA Electronics Europe GmbH | Data subject to change without notice.
EN, 2019/01/22