Outdoor Water-resistant AI PoE Switch


SF-SW8FE2GE-2BT-120W-OUT

- Total 120W Power Supply
- 8 ports PoE
- 2 ports Uplink

Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power
- Auto-Adaption 250m Transmission

Ports Description



1 100Mbps PoE Ports
2 bt 60W Power Ports
3 1000Mbps Uplink Ports

Dimension (mm)



Installation Diagram

Wall Mounted



Hoop Mounted



Mounting ear Wall Mounted



Specifications

Model	SF-SW8FE2GE-2BT-120W-OUT
Ports	PoE (1~6):10/100Mbps PoE ports (RJ45) PoE (7~8):10/100Mbps PoE ports (RJ45),Support bt 60W High Power LAN (1~2):10/100/1000Mbps uplink ports (RJ45)
Transmission Rate	1000Mbps: Full Duplex Only; 10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	100Mbps /10Mbps, Auto-Adaption 250m
Performance Specification	Bandwidth:5.6Gbps
	Network Latency (10 to 1000Mbps):≤16μs (use the 64byte package size)
	MAC address table: 8K
	Packet Forwarding Rate: 4.2Mpps
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total≤120W AI Watchdog: Port 1~8 Power Output: PoE1~6 Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 310mm*260mm*100mm, Weight: 1.6KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable, User Manual, Installation Kits (Steel hoops, Waterproof pipes, Wall mounting earrings)

※Specifications subject to change without notice.