HDMI-SPL-1x2-4K30-CAT6-L
Product specification

Part No.		HDMI-SPL-1x2-4K30-CAT6-L
Item		**Specification**
Mode		1 in 2 out
HDMI Perfomance	Compatibility	HDMI 1.4，HDCP1.4
	Resolution	800x600, 1024x768, 1280x720, 1280x960, 1366x768, 1440x900, 1680x1050, 1920x1080, 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@24/25/30/50/60Hz, 4K@24/25/30Hz
	Audio Formats	PCM, LPCM, Dolby Digital 5.1CH, Dolby TrueHD 5.1CH
Transmission distance	CAT6/6A/7	1080p@60Hz≤70 meters 4K@30Hz≤40 meters
IR Passback	IR passback (20-60khz)	
RS-232	3Pin：GND-RxD-TxD，follows RS-232 levels Default baud rate：9600	
Operating Environment	Working temperature	-20~60℃
	Storage temperature	-30~70℃
	Humidity	0~90% RH
Protection	ESD protection 1a Contact discharge level 2 (±4KV) 1b Air discharge level 3 (±8KV) Implementation of the standard: IEC61000-4-2	
	Lightning protection	
	Surge protection	
Power	Supply	TX: DC12V/1A
	Consumption	TX+RX＜11W
Physical Properties	Housing	Iron
	Color	Black
	Weight	TX: 250g RX: 115g x2
	Dimensions	TX: 151.5(L) x 86.5(W) x 19.0(H)mm RX: 75.0(L) x 60.0(W) x 16.5(H) mm